

# **AUTOFLEX POWERED TUGGER**

## **THE PERFECT ASSISTANT FOR MOVING CONVEYORS!**

The integrated AUTOFLEX POWERED TUGGER makes pulling AUTOFLEX conveyors in and out of trailers a breeze. Longer runs of conveyors and steep dock plates can require more effort to push and pull conveyors in and out of the dock trailer. AUTOFLEX POWERED TUGGER features an ergonomic yet powerful solution to safely help and assist with the maneuverability of AUTOFLEX conveyors.

**"Twist Grip" Throttle** allows for both forward and reverse speed to be precisely dialed in when assisting the operator with movement.

### **PRODUCT SPECIFICATIONS:**

- LOAD CAPACITY 50LBS. PER FT 100LBS. PER ZONE
- PUSH/PULL SPEED 0-100 FPM
- BOTH FORWARD AND REVERSING
- INTEGRATED INTO STANDARD AUTOFLEX1.9 MODULES (NO FIELD CONNECTION OR INSTALLATION)
- ROLLER DIAMETER 1.9INCHES
- 5INCH AXLE CENTERS STANDARD 3" AND 4" CENTERS AVAILABLE
- 31" TOP OF ROLLER TO 38.5" TOR ADJUSTABLE HEIGHT
- STEEL CONSTRUCTION, GALVANIZED FRAME, PAINTED RAL9010 WHITE
- PACKAGE STOP SENSING INCLUDED
- YELLOW ILLUMINATED PUSHBUTTON FOR SPEED CONTROL AT INFEEED AND DISCHARGE OF EACH MODULE
- RED/ GREEN ILLUMINATED START/ STOP PUSHBUTTON LOCATED AT INFEEED AND DISCHARGE OF EACH MODULE
- E-STOP FOR PUSH/PULL FUNCTION
- 7 CONVEYOR SPEEDS SELECTABLE UP TO 115FPM
- 8" FIXED PNUMATIC REAR TIRES AND 8"STEERING SWIVAL CASTER

## **CONTACT MILWAUKEE CONVEYOR**

### **FOR MORE INFO!**

www.milwaukeeconveyor.com  
N8069 COUNTY HWY F #109 IXONIA, WI 53036  
[info@milwaukeeconveyor.com](mailto:info@milwaukeeconveyor.com)  
262.527.3029



### **STANDARD PRODUCT OPTIONS**

(3" AND 4" CENTERS AVAILABLE UPON REQUEST)

MCAFPT-5-30	• AUTOFLEX POWERED TUGGER, 30IN WIDE ROLLERS, 5IN C-C ROLLER DISTANCE. FACTORY INTEGRATED INTO AUTOFLEX CONVEYOR EQUIPMENT.
MCAFPT-5-24	• AUTOFLEX POWERED TUGGER, 24IN WIDE ROLLERS, 5IN C-C ROLLER DISTANCE. FACTORY INTEGRATED INTO AUTOFLEX CONVEYOR EQUIPMENT.

