

AUTOFLEX 1.9 POWERED FLEXIBLE CONVEYOR ACCUMULATION

ACCUMULATING CONVEYOR SOLUTIONS ARE BEST UTILIZED WHEN SORTING, SCANNING, OR CLIENT EQUIPMENT INTEGRATION IS REQUIRED.

MILWAUKEE CONVEYOR 1.9 POWERED *AUTOFLEX ACCUMULATION* PROVIDES CUSTOMERS WITH THE ULTIMATE FLEXIBILITY IN CONVEYANCE. PRIMARILY USED FOR QUICKLY LOADING AND UNLOADING PACKAGES IN AND OUT OF TRAILERS SAFELY, *AUTOFLEX ACCUMULATION* CAN BE BEST UTILIZED WHEN PACKAGE SPACING IS REQUIRED FOR SCANNING, SORTING, OR INTERFACING WITH CLIENT EQUIPMENT. IT ALSO A CONVENIENT OPTION FOR TEMPORARY AND PERMANENT ASSEMBLY LINES, PEAK/SEASONAL CONVEYANCE, AND CAN BE VERY USEFUL IN SPACING OUT WORK AREAS. WITH SIMPLE MOBILITY AND FLEXIBILITY, *AUTOFLEX* CAN EASILY ADAPT TO MANY APPLICATIONS AS IT'S EASY TO EXPAND, TURN, CONTRACT AND QUICKLY MOVE TO OTHER AREAS AND STORE AWAY AS NEEDED.

STANDARD LENGTHS:

STANDARD SYSTEMS EXPANDED

- PARENT 21'-2"L
- PARENT 38'-4"L
- PARENT + CHILD-1 59'-11"L
- PARENT + CHILD-1 77'-1"L
- PARENT + CHILD-1 + CHILD-2 98'-8"L
- PARENT + CHILD-1 + CHILD-2 115'-10"L

STANDARD FEATURES:

- WIDTHS: 30" (24" OPTIONS AVAILABLE)
- 3 SELECTABLE CONVEYOR MODES: SINGULATE, TRAIN RELEASE, TRANSPORTATION
- ILLUMINATED MODE INDICATOR LIGHT
- ZONES UP TO 48" EXPANDED
- SENSORS BARS INCLUDE (6) SENSORS PER BAR 30"W (4) SENSORS 24"W
- EACH UNIT CAN BE CONFIGURED AS A PARENT OR CHILD
- INPUT AND OUTPUT INTERLOCK SOCKETS INCLUDED
- PUSH-BUTTON CONTROL ON INFEEED AND DISCHARGE
- END OF LINE SENSING INCLUDED
- HANDLES AT EVERY LEG SUPPORT
- 24VDC BRUSHLESS MOTOR TECHNOLOGY
- PULL BAR AT LOAD/ UNLOAD END
- HOOK AND ROD COUPLERS FOR MECHANICAL CONNECTIONS
- 7/8 MALE AND FEMALE PLUGS FOR CONNECTING MULTIPLE SYSTEMS

KEY BENEFITS

FEATURES 3 SELECTABLE OPERATION MODES. SINGULATE, TRAIN RELEASE, AND TRANSPORTATION

ALLOWS FOR UNIFORM PACKAGE SPACING WITH INDEPENDENTLY CONTROLLED ZONES

RECONFIGURE, LINK ADDITIONAL SYSTEMS, OR USE INDEPENDENTLY

STANDARD SPECIFICATIONS

- CAPACITY 50LBS. PER FT. / 100LB PER ZONE
- 7 SPEED SELECTIONS AT OPERATOR CONTROL UP TO 115FPM
- HEIGHT ADJUSTMENT 28.5" - 38.5"
- 6" LOCKING CASTERS ON EVERY WHEEL
- OPERATOR CONTROL- START, STOP, SPEED
- PARENT/ CHILD MODE SELECTOR SWITCH
- 5" CENTERS STANDARD (3" & 4" CENTERS AVAILABLE)

CONTACT MILWAUKEE CONVEYOR TO LEARN MORE ABOUT *AUTOFLEX 1.9*

FOR DISTRIBUTORS AND INTEGRATORS IN YOUR AREA CALL TODAY!

MILWAUKEE CONVEYOR
N8069 COUNTY ROAD F #109
IXONIA, WI 53036
JOCAIN@MILWAUKEECONVEYOR.COM
262-527-3029

WWW.MILWAUKEECONVEYOR.COM



STANDARD MODULE SPECIFICATION CONT.
(*STOCK ITEMS INDICATED IN YELLOW BELOW)

24" ROLLER WIDTH		30" ROLLER WIDTH		APPROX. CONV LENGTH	
MODEL#	LEG QTY.	MODEL#	LEG QTY.	EXT	CON
MCAF1.92421PA	8	MCAF3021PA	8	21'-2"	10'-4"
MCAF1.92438PA	13	MCAF1.93038PA*	13	38'-4"	17'-8"
MCAF1.92459PCA	21	MCAF1.93059PCA	21	59'-11"	28'-5"
MCAF1.92477ACA	26	MCAF1.93077PCA*	26	77'-1"	35'-9"
MCAF1.92498PCCA	34	MCAF1.93098PCCA	34	98'-8"	46'-5"
MCAF1.924115PCCA	39	MCAF1.930115PCCA*	39	115'-10"	53'-10"

