

AUTOFLEX 1.9 POWERED FLEXIBLE CONVEYOR TRANSPORTATION

A CONVENIENT, SAFE POWERED FLEXIBLE CONVEYOR SOLUTION FOR LOADING, UNLOADING, TRANSPORTING, AND ASSEMBLY.

MILWAUKEE CONVEYOR 1.9 POWERED *AUTOFLEX* PROVIDES CUSTOMERS WITH THE ULTIMATE FLEXIBILITY IN CONVEYANCE. PRIMARILY USED FOR QUICKLY LOADING AND UNLOADING PACKAGES IN AND OUT OF DOCK TRAILERS SAFELY, *AUTOFLEX* IS ALSO A CONVENIENT OPTION FOR TEMPORARY AND PERMANENT ASSEMBLY LINES, PEAK/SEASONAL CONVEYANCE, AND CAN BE VERY USEFUL IN SPACING OUT WORK AREAS. WITH SIMPLE MOBILITY AND FLEXIBILITY, *AUTOFLEX* CAN EASILY ADAPT TO MANY APPLICATIONS AS IT'S EASY TO EXPAND, TURN, CONTRACT AND QUICKLY MOVE TO OTHER AREAS AND STORE AWAY AS NEEDED.

STANDARD LENGTHS:

STANDARD SYSTEMS EXPANDED

- PARENT 22'L
- PARENT 40'L
- PARENT + CHILD-1 60'L
- PARENT + CHILD-1 80'L
- PARENT + CHILD-1 + CHILD-2 100'L
- PARENT + CHILD-1 + CHILD-2 120'L

STANDARD FEATURES:

- WIDTHS: 30" (24" OPTIONS AVAILABLE)
- EACH UNIT CAN BE CONFIGURED AS A PARENT OR CHILD
- INPUT AND OUTPUT INTERLOCK SOCKETS INCLUDED
- PUSH-BUTTON CONTROL ON INFEED AND DISCHARGE
- END OF LINE SENSING INCLUDED
- HANDLES AT EVERY LEG SUPPORT
- 24VDC BRUSHLESS MOTOR TECHNOLOGY
- PULL BAR AT LOAD/ UNLOAD END
- HOOK AND ROD COUPLERS FOR MECHANICAL CONNECTIONS
- 7/8 MALE AND FEMALE PLUGS FOR CONNECTING MULTIPLE SYSTEMS

KEY BENEFITS

LOAD/ UNLOAD PRODUCT SAFELY, QUICKLY, AND EFFICIENTLY

PORTABILITY MAKES IT EASY TO RELOCATE AND/OR STORE AWAY

RECONFIGURE, LINK ADDITIONAL SYSTEMS, OR USE INDEPENDENTLY

STANDARD SPECIFICATIONS

- CAPACITY 50LBS. PER FT. / 100LB PACKAGES
- 7 SPEED SELECTIONS AT OPERATOR CONTROL UP TO 115FPM
- HEIGHT ADJUSTMENT 28.5" - 38.5"
- 6" LOCKING CASTERS ON EVERY WHEEL
- OPERATOR CONTROL- START, STOP, SPEED
- PARENT/ CHILD MODE SELECTOR SWITCH
- 5" CENTERS STANDARD (4" CENTERS AVAILABLE)

CONTACT MILWAUKEE CONVEYOR TO LEARN MORE ABOUT *AUTOFLEX 1.9*

FOR DISTRIBUTORS AND INTEGRATORS IN YOUR AREA CALL TODAY!

MILWAUKEE CONVEYOR
 N8069 COUNTY ROAD F #109
 IXONIA, WI 53036
 JOCAIN@MILWAUKEECONVEYOR.COM
 262-527-3029
WWW.MILWAUKEECONVEYOR.COM



STANDARD MODULE SPECIFICATIONS CONT. (*STOCK ITEMS INDICATED IN YELLOW)

24" ROLLER WIDTH		30" ROLLER WIDTH		APPROX. CONV LENGTH	
MODEL#	LEG QTY.	MODEL#	LEG QTY.	EXT	CON
MCAF1.92422PT	8	MCAF3022PT	8	22'	10'
MCAF1.92440PT	13	MCAF1.93040PT*	13	40'	17'
MCAF1.92460PCT	21	MCAF1.93060PCT	21	60'	27'
MCAF1.92480PCT	26	MCAF1.93080PCT*	26	80'	34'
MCAF1.924100PCCT	34	MCAF1.930100PCCT	34	100'	44'
MCAF1.924120PCCT	39	MCAF1.930120PCCT*	39	120'	52'

